CT300
Frame with EMV for Apple iPad Air 2
CTG2F005

Select Audible/ Silent Alarm Mode:

Note: Default is audible alarm.

1. Place handle half of frame on stand.

2. LED indicates current alarm mode.

3. Push and hold frame button for approximately 5 seconds. You will see LED change colors and tone will sound multiple times to indicate change of mode.

Software Controlled Undock

If using only key programming, proceed to next step.

If using InVue CT300 Undock Application, download it from the iTunes Store now. Follow in app instructions for setup.

If using InVue's software development kit, follow your IT department's guidelines for setup.

Please be sure you have updated the Bluetooth drivers on your tablet prior to use with your CT300 system

Frame Assembly:

6. Connect Apple Lightning cable (CTG2P005) to frame cable.

7. Tuck connector end of Apple Lightning cable into holding ribs in end of frame.

8. Slide iPad into handle side of frame, then slide frame halves together, ensuring Lightning connector is inserted in tablet.

9 Using a Phillips 1 screwdriver, secure frame halves from rear with two M3 screws provided.

Ensure screws are fully seated into frame or docking mechansim can be damaged.

10 Remove back cover of the Ingenico iSMP reader by sliding top half up and lifting out.

11 Remove InVue cover provided.

12 Replace back cover of Ingenico iSMP with InVue cover provided.

13 Slide Ingenico iSMP with Invue back cover into holder. (Clicks when fully seated)

Optional:

Using a Philips 1 screwdriver, secure EMV to holder with M2 screw provided.

Fold back EMV when not in use.

SD0367 Rev0 05/15/16

www.invue.com

NA / LATAM // 704.752.6513 • 888.55.INVUE
EMEA // +31.23.8900150
APAC // +852.3127.6811

© 2016 InVue Security Products Inc. All rights reserved.
InVue is a registered trademark of InVue Security Products.